

PRO-setral-PL 941 (Spray)	Nr. 0575
Grease-like anti-corrosion for temporary protection.	Packaging: 400ml aerosol other packaging on request

Application

Especially developed for the temporary preservation of injection moulds and tools.

Characteristics

- Excellent corrosion protection
- From injection moulding tools completely removed after a short no. of shots
- Extremely water repellent
- Short drying time
- Easy application
- Silicone-free
- Economical in consumption

Method of use

- Do not apply on hot surfaces. Heat decomposes the product and an optimal corrosion protection cannot be guaranteed.
- Apply thin and evenly on cleaned points.
- Clean and degrease lubrication points carefully prior to application. For this CLEAN-setral-AN/U spray is specially suited.
- Shake well prior to use (spray).
- The minimum shelf life in original sealed containers, stored in a cool and dry place (no direct sunlight) is about 2 years.

Technical data

Colour	transparent, light yellow		DIN ISO 2049
Basis	corrosion protection in solvents		
Density 15°C	0.785	g/cm ³	DIN ISO 51757
Copper corrosion, 24h/100°C	0	rating	DIN 51811
Corrosion test 100h	0 - no corrosion		DIN 51359
VbF	A I		

Setral Chemie GmbH
Salzsteinstrasse 4
D-82402 Seeshaupt
Telefon: +49 (0) 88 01 97 10
Telefax: +49 (0) 88 01 97 30
Email: info@setral.net

Sétral S.á.r.l.
13, rue Tannmuhle
F-67310 Romanswiller
Téléphone: +33 (0) 3 88 59 11 59
Télécopie: +33 (0) 3 88 59 11 57
Email: france@setral.net

The information in this bulletin is, to our knowledge, true and accurate, but all recommendations are without guarantee, since the conditions of use are beyond our control. Setral disclaims any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.