

# COLD GALVANISING PRODUCTS

Most IDEAL PRODUCTS for HOT DIP GALVAIZERS  
STEEL FABRICATORS using GALVANIZED IRON

## Available in two versions & sold in aerosol & bulk:

- Pure Zinc
- Zinc-Al. formulations

## Salient Features

- Dry to touch in 2-10 minutes & complete cure in 2 Hours
- Over Coating Period: After 24 Hours.
- Coverage: 10-12 m<sup>2</sup>/Lt
- Excellent Cross Cut Adhesion & Flexibility
- Passes 800 Hours in Salt Spray test in Fog chamber
- Coating thickness: 18-20 microns in single spray

## Applications:

- Transmission Line Towers, Lightening poles; telecom towers.
- Scaffoldings, Cable Trays, Gratings, Railings, steel Buildings, MS fabrications.
- Power-plant equipments & sub-station equipments.
- Chemical & Petrochemical plants, off-shore platforms, oil Rigs
- HVAC, Air-Conditioning Ducts, Home and Industrial Appliances ETP plants, chemical pipelines, steam pipelines, transformers.
- Hot-dip galvanizing plants; bridge sections, airport Hangers
- Power generation and distribution, tower erection & maintenance
- Auto-Underbody & exhaust pipes, MS Parts in very corrosive fields.

